

ALIZE15000STDE: Portable Power Genset Range PRESTIGE

Main use ideal for worksite in urban areas and mobile trade.

- Very silent
- Very large autonomy
- Longlife engine
- Electric start
- Full control panel



AUTOMATIC VOLTAGE REGULATION

This ensures that the voltage output from the generator set remains within $\pm 2\%$ of the rated voltage. By comparison, a generator set without such a device generally runs at $\pm 10\%$ of its rated voltage.

GENERAL SPECIFICATIONS

Frequency	50
Max power W	12000
Max power VA	15000
Noise level in Lwa	86

ALTERNATOR SPECIFICATIONS

Type	MECC-ALTE ECO28S
Regulation	Without ring and brush
Protection class	IP 23
Insulation class	Class H

ENGINE SPECIFICATIONS

Brand	Mitsubishi
Type	S4 L2 SD
Distribution	Water-cooling-1500 tr/mn
Starting	Electrical start
Fuel	Diesel Oil
Run time (h)	14.7
Fuel consumption (l/h)	3.1
Tank (l)	50
Oil guard	Engine shut down on lack of oil pressure
Cubic capacity (cm ³)	1318
Oil capacity (l)	3.7

SOCKETS AND PANEL

1 x 10/16A 230V domestic - circuit breaker + 1 x 16A 230V CEE 2P+T - circuit breaker + 1 x 32A 230V CEE 2P+T - circuit breaker - voltmeter - ammeter - emergency stop button - hours counter - selector support light - Lights test button - battery charging light - water temperature fault indicator - oil pressure fault indicator

DIMENSIONS AND WEIGHT

LxWxH Dimensions (cm)	175 x 77.5 x 123
Weight (kgs)	570