

## ALIZE6000SDE: Portable Power Genset Range PRESTIGE

Main use ideal for worksite in urban areas and mobile trade (with sand filter).

- Very silent
- Very large autonomy
- Longlife engine
- Electric start
- Full control panel



### AUTOMATIC VOLTAGE REGULATION

This ensures that the voltage output from the generator set remains within  $\pm 2\%$  of the rated voltage. By comparison, a generator set without such a device generally runs at  $\pm 10\%$  of its rated voltage.

### GENERAL SPECIFICATIONS

Frequency	50
Max power W	6000
Max power VA	7500
Noise level in Lwa	85

### ALTERNATOR SPECIFICATIONS

Type	MECC-ALTE ECO3-2S
Regulation	Without ring and brush
Protection class	IP 23
Insulation class	Class H

### ENGINE SPECIFICATIONS

Brand	Mitsubishi
Type	L3E SD
Distribution	Water-cooling-1500 tr/mn
Starting	Electrical start
Fuel	Diesel Oil
Run time (h)	22.5
Fuel consumption (l/h)	1.6
Tank (l)	36
Oil guard	Engine shut down on lack of oil pressure
Cubic capacity (cm <sup>3</sup> )	
Oil capacity (l)	3.6

### SOCKETS AND PANEL

1 x 10/16A 230V domestic - circuit breaker + 1 x 16A 230V CEE 2P+T - circuit breaker + 1 x 32A 230V CEE 2P+T - circuit breaker - voltmeter - ammeter - emergency stop button - hours counter - selector support light - Lights test button - battery charging light - water temperature fault indicator - oil pressure fault indicator

### DIMENSIONS AND WEIGHT

LxWxH Dimensions (cm)	144 x 66 x 83
Weight (kgs)	368



This product is QUALIGEN certified.

Defined by the SIMOTHERM and GIGREL professional organisations, the QUALIGEN charter is intended to provide a label for equipment compliant with current regulations (user safety, noise level, power, sales information, After-sales service)