

HX3000: Portable Power Genset Range INTENS

Genset for professional use: Intensive worksite and/or difficult conditions.

- Solid and compact frame
- OHV Honda professional engine
- Oil level safety
- Circuit breaker



GENERAL SPECIFICATIONS

Frequency	50
Max power W	3000
Max power VA	3750
Noise level in Lwa	95

ALTERNATOR SPECIFICATIONS

Type	MECC-ALTE S16W90
Regulation	Without ring or brush
Protection class	IP 23
Insulation class	Class H

ENGINE SPECIFICATIONS

Brand	Honda
Type	GX 200
Distribution	O.H.V.
Starting	Hand start
Fuel	Unleaded Petrol
Run time (h)	2.7
Fuel consumption (l/h)	1.3
Tank (l)	3.6
Oil guard	Engine shut down on low oil level
Cubic capacity (cm ³)	196
Oil capacity (l)	0.6

SOCKETS AND PANEL

2 x 10/16A 230V domestic - circuit breaker

DIMENSIONS AND WEIGHT

LxWxH Dimensions (cm)	59 x 46 x 43
Weight (kgs)	41



This product is QUALIGEN certified.

Defined by the SIMOTHERM and GIGREL professional organisations, the QUALIGEN charter is intended to provide a label for equipment compliant with current regulations (user safety, noise level, power, sales information, After-sales service)